

TABLE OF CONTENTS

CHAPTER NO	TOPIC	PAGE NO
CHAPTER I	1. INTRODUCTION	1
	1.1. History of AM	1
	1.2. Transformation from Rapid Prototyping RP to AM	2
	1.3. Additive Manufacturing Growth Rate	3
	1.4. Differences in Manufacturing Using Additive (AM) Subtractive Manufacturing (SM) and its Domination	4
	1.4.1. Manufacturing Regions	4
	1.4.2. High Production Volume based Manufacturing: Mass Manufacturing, Mass Complexity and Mass Customization	4
	1.4.3. Low Production Volume Manufacturing – Complexity for Free with Additive Manufacturing	5
	1.5. Additive Manufacturing and its Application Levels	6
	1.5.1. Rapid Prototyping	6
	1.5.2. Rapid Manufacturing	6
	1.6. Sustainable Manufacturing in Additive Manufacturing	7
	1.7. Steps Involved in Additive Manufacturing	7
	1.7.1. Conceptualization of Model and CAD	8
	1.7.2. Reverse Engineering (RE)Technology	8
	1.7.3. Computer-Aided Engineering	9
	1.7.4. Haptic-Based CAD	9
	1.7.5. Conversion to STL, Transfer to AM Machine and STL File Manipulation	10
	1.7.6. Machine Setup	11
	1.7.7. Build	11
	1.7.8. Removal	11
	1.7.9. Post-processing of Part or Product	11
	1.8. Application	11
	1.8.1. AM in Aerospace & Defence	12

	1.8.2. AM in Medical Field	13
	1.8.3. AM in Automotive Field	14
	1.9. General Factors in Design Considerations for 3D Printing	14
	1.9.1. Overhangs	14
	1.9.2. Wall Thickness	14
	1.9.3. Warping	15
CHAPTER II	2. ADDITIVE MANUFACTURING TECHNIQUES	17
	2.1. Stereo Lithography (SLA)	19
	2.1.1. Principle	19
	2.1.2. Construction and Working	19
	2.1.3. Free and Constrained Surface Approach	21
	2.1.4. Advantages	22
	2.1.5. Disadvantages	22
	2.1.6. Applications	22
	2.1.7. Comparison of various available Stereo Lithography Systems	23
	2.2. Fused Deposition Modelling (FDM)	23
	2.2.1. Principle	23
	2.2.2. Construction and Working	24
	2.2.3. Materials used for FDM	25
	2.2.4. Advantages	26
	2.2.5. Disadvantages	26
	2.2.6. Applications	26
	2.2.7. Commercially available FDM Machines	26
	2.3. Laminated Object Manufacturing (LOM)	27
	2.3.1. Principle	27
	2.3.2. Construction and Working	27
	2.3.3. Materials used for LOM	29
	2.3.4. Advantages	29
	2.3.5. Disadvantages	29
	2.3.6. Applications	29
	2.4. Selective Laser Sintering (SLS)	30
	2.4.1. Principle	30

	2.4.2. Construction and Working	31
	2.4.3. Materials for SLS	32
	2.4.4. Advantages	32
	2.4.5. Disadvantages	33
	2.4.6. Applications	33
	2.4.7. Commercially available SLS Machines	34
	2.5. Laser Engineered Net Shaping (LENS)	35
	2.5.1. Principle	35
	2.5.2. Construction and Working	35
	2.5.3. Materials used for LENS	36
	2.5.4. Advantages	36
	2.5.5. Disadvantages	36
	2.5.6. Applications	37
	2.5.7. Commercially available LENS Machines	38
	2.6. Electron Beam Melting (EBM)	38
	2.6.1. Principle	38
	2.6.2. Construction and Working	39
	2.6.3. Materials for EBM Process	39
	2.6.4. Advantages	40
	2.6.5. Disadvantages	40
	2.6.6. Applications	40
	2.6.7. Commercially available EBM Machines	41
CHAPTER III	3. SELECTIVE LASER MELTING (SLM)	46
	3.1. Introduction	46
	3.2. Principle	46
	3.3. Working Process	46
	3.4. Features Attained Using SLM Process	47
	3.5. Components of SLM Machine	48
	3.6. Factors to be Considered in SLM	50
	3.6.1. Process Related Factors	51
	3.6.2. Laser Related Factors (Laser Power, Scanning Speed, Layer Thickness, Scan Line Spacing)	51

	3.6.3. Scanning Strategies	53
	3.6.4. Material Related Factors	53
	3.6.5. Powder Bed Related Factors	54
	3.7. General Considerations for Supports Design in Metal SLM	55
	3.7.1. Part Geometry	55
	3.7.2. Build Orientation	56
	3.7.3. Supports	56
	3.7.4. Sacrificial Geometries	58
CHAPTER IV	4. SELECTIVE LASER MELTING (SLM) OF ALUMINIUM (AL) ALLOYS	61
	4.1. Introduction	61
	4.1.1. Strength to Weight Ratio	61
	4.1.2. Corrosion Resistance	61
	4.1.3. Electrical and Thermal Conductivity	62
	4.1.4. Toxicity	62
	4.1.5. Recycling	62
	4.1.6. Applications	62
	4.2. Densification Behaviour based on Laser Related Process Parameter	62
	4.3. Densification Behaviour based on Powder Related Properties	70
	4.4. Defects in SLM of Aluminium Alloys	71
	4.4.1. Porosity	71
	4.5. Mechanical Properties of SLMed Part or Component	73
	4.6. Tribological behaviour of SLMed Parts	82
CHAPTER V	5. SELECTIVE LASER MELTING (SLM) OF MAGNESIUM (MG) ALLOYS	86
	5.1. Introduction	86
	5.1.1. Application of Magnesium	86
	5.1.2. Structural Applications	86
	5.1.3. Electronic Applications	87
	5.1.4. Medical Applications	87

	5.2. Densification Behaviour based on Laser Related Process Factors	87
	5.3. Defects in SLM of Magnesium Alloys	89
	5.4. Mechanical Properties of SLMed Part or Component	90
	5.4.1. Hardness	90
	5.4.2. Tensile Strength	96
	5.5. Tribological Behaviour of SLMed Part or Component	98
	5.5.1. Corrosion	98
	5.5.2. Wear	102
CHAPTER VI	6. SELECTIVE LASER MELTING (SLM) OF TITANIUM (TI) ALLOYS	105
	6.1. Introduction	105
	6.2. Properties of Titanium	106
	6.2.1. Strength to Weight Ratio	106
	6.2.2. Corrosion Resistant	106
	6.2.3. Refractoriness	107
	6.2.4. Biocompatibility	107
	6.2.5. Health Effects of Titanium	108
	6.2.6. Environmental Effects of Titanium	108
	6.3. Applications	108
	6.3.1. Aerospace Industry	108
	6.3.2. Marine Equipments	109
	6.3.3. Sports Applications	109
	6.3.4. Medical Industry	109
	6.3.5. Pyrotechnics	109
	6.3.6. Pigment	109
	6.3.7. Jewellery	109
	6.4. Densification Behaviour based on Laser Related Factors	109
	6.5. Mechanical Properties of SLMed Part	114
	6.5.1. Hardness	114
	6.5.2. Fatigue	116
	6.5.3. Creep	121
	6.5.4. Tensile Strength	123

	6.6. Tribological Behaviour of SLMed Parts	125
	6.6.1. Wear	125
	6.7. Defects in SLM of Titanium Alloys	127
	6.7.1. Crack	127
	6.7.2. Porosity	129
CHAPTER VII	7. SELECTIVE LASER MELTING (SLM) OF INCONEL (NI BASED ALLOY)	134
	7.1. Introduction	134
	7.1.1. Characteristics of Inconel	135
	7.2. Applications of Inconel	135
	7.2.1. Oil & Gas Extraction	136
	7.2.2. Heat Treatment Applications	136
	7.2.3. Rapid Temperature Changes	136
	7.2.4. Saltwater Applications	136
	7.2.5. Jet Engines	136
	7.3. Densification Behaviour based on Laser Related Process Factors	137
	7.4. Sustainability of Ni based Alloy	141
	7.5. Mechanical Properties of SLMed Parts	147
	7.5.1. Hardness	147
	7.5.2. Impact Strength	148
	7.5.3. Fatigue	149
	7.6. Tribological Behaviour of SLMed Parts	152
	7.6.1. Wear	152
	7.6.2. Corrosion	156
	7.7. Defects in SLM of Ni based Alloys	162
	7.7.1. Micro Crack and Porosity	162
CHAPTER VIII	8. SELECTIVE LASER MELTING (SLM) OF STAINLESS STEEL	169
	8.1. Introduction	169
	8.2. Densification Behaviour based on Laser Related Process Factors	171

	8.3. Biocompatibility of Stainless Steel with Respect to Scanning Strategy	180
	8.4. Sustainability of Steel Powders	184
	8.5. Mechanical Properties of SLMed Parts	188
	8.5.1. Hardness	188
	8.5.2. Tensile Strength	190
	8.6. Tribological behaviour of SLMed Parts	191
	8.6.1. Friction and Wear	191
	8.6.2. Corrosion	200
CHAPTER IX	9. SELECTIVE LASER MELTING (SLM) OF COMPOSITES	205
	9.1. Introduction	205
	9.2. Mechanical Properties of Composites	207
	9.2.1. Particle Reinforcement	207
	9.2.2. Continuous Fiber Reinforcement	207
	9.2.3. The Effect of Fiber Orientation	207
	9.2.4. Mechanical Properties various Materials	207
	9.3. Applications of Composites	208
	9.3.1. Aerospace	208
	9.3.2. Automotive/ Transportation/ Farm/ Construction/ Infrastructure	208
	9.3.3. Corrosive Environments in Chemical Industries	209
	9.3.4. Marine	209
	9.4. Densification Behaviour based on Laser Related Process Factors	209
	9.5. Defects in SLM of Composites	211
	9.5.1. Porosity	211
	9.5.2. Crack	214
	9.6. Mechanical Properties of SLMed Part or Component	217
	9.6.1. Hardness	217
	9.6.2. Tensile Strength	218
	9.7. Tribological Behaviour of SLMed Parts	223
	9.7.1. Wear	223
	9.7.2. Corrosion	224

CHAPTER X	10. CONCLUSION AND FUTURE SCOPE	230
	10.1. Conclusion	230
	10.2. Future Scope	230

LIST OF TABLES

TABLE NO.	DESCRIPTION	PAGE. NO
1.1	History of AM	2
1.2	Transformation of Rapid Prototyping (RP) to AM	2
2.1	Comparison of the Stereo Lithography System in Market	23
2.2	Materials used for Material Extrusion Technique (FDM)	25
2.3	FDM Machines with its Specifications	27
2.4	Available SLS Machines with its Specifications	34
2.5	Commercially available LENS Systems	38
2.6	Commercially available EBM Machines from Arcam	41
3.1	Significant Process Related Factors of SLM Process	51
4.1	Orthogonal Array L18	63
4.2	ANOVA for Density	64
4.3	ANOVA for Porosity	72
4.4	ANOVA for Microhardness	73
4.5	Powder Characteristics	77
4.6	Effect of Particle Size and Heating Rate on Density and Tensile Properties of Al-Cu Alloy	78
4.7	Mechanical Properties of SLM Built Parts and Cast + Aged Parts	80
4.8	Charpy Impact Testing Values	81
5.1	Laser Parameters Employed for LSM of MEZ	92
5.2	Parameters of LSM	94
5.3	Corrosion Rate and Polarization Resistance of MEZ in a 3.56 wt.% NaCl Solution	101
5.4	Electrochemical Test Values for Corrosion	102
6.1	Process Parameters for SLM Process	113
6.2	Hatch Parameters	113
6.3	Process Parameter HIP for TiAL6V4	114
6.4	Parameters for SLM Processed Ti6Al4V (Ti Alloy Part)	116
6.5	Tensile Results for SLM and EBM Produced Ti Alloy Samples	124
6.6	CT Results of Non-HIP ed Samples	130

6.7	CT Results of HIP ed Samples	130
7.1	Flow Characteristics of IN728	138
7.2	Chemical Composition of the IN718 Powder	142
7.3	SLM Process Parameters Carried Out on Static Tensile and Fatigue Samples	151
7.4	Fatigue Data, Fully Reversed Tensile Loads (R=-1)	152
7.5	Chemical Compositions of Inconel 718 Powder (%wt.)	153
7.6	Chemical Composition of Inconel 718 Powders after Process	157
7.7	Heat Treatment Process of Inconel 718 Produced by SLM	157
7.8	Electrochemical Test Parameter Variables	158
7.9	EIS Measurement Readings	161
7.10	SLM Process Parameters for Inconel 625 Specimens	163
8.1	Usage of Stainless Steel	171
8.2	Characteristics of Work Piece after Processing with some of Smooth Tracks and Irregular Tracks Conditions	178
8.3	Composition of SS316L (Wt%)	180
8.4	Particle Analysis of the M3:2 Steel Powder in the Initial and in the Reused States (after 30 cycles)	186
8.5	Comparison of M3: 2 High Speed Steel Powders	187
8.6	Fracture Toughness Value for different Build Directions	189
8.7	Vickers Hardness Results of SS316L	190
8.8	Tensile Test Results for different Build Directions	191
8.9	Process Parameter for Sample Preparation	192
8.10	Property of Hydraulic Oil Used in Tests	193
9.1	Comparison of Cost, Specific Strength, and Specific Stiffness	208
9.2	Chemical Composition (in weight %) of the Standard Alloys	211
9.3	Comparison of Vickers Hardness of Ti Materials	218
9.4	Compressive Properties of Biomedical Ti Materials	222
9.5	Potentiodynamic Polarization Curve Parameter Values	226

LIST OF FIGURES

FIGURE NO.	DESCRIPTION	PAGE NO.
1.1	Growth of Additive Manufacturing Industries	3
1.2	General 3D Printing Process Steps	8
1.3	Additive Manufacturing in various Industrial and Service Sectors	12
1.4	Injector Head for Ariane 6 Launcher	13
1.5	Applications of AM in Implants, Prosthetics and Organ Printing	13
1.6	Bracket Manufactured Using AM Technologies	14
2.1	Representation of Life Cycle of Product	17
2.2	Various AM Process	18
2.3	Typical SLA Process Machine	20
2.4	Application of SLA in various Fields	22
2.5	Schematic Process of FDM	24
2.6	Components Produced by FDM Process	26
2.7	Schematic Layout of LOM Process	28
2.8	Products made by LOM Process	30
2.9	Schematic Layout of SLS Process	31
2.10	Prototypes, Patterns for Casting etc. Produced by SLS	34
2.11	Schematic Layout of LENS Process	36
2.12	Areas where LENS Process is used for Producing Parts	37
2.13	Schematic Layout of EBM Process	39
2.14	Application of EBM in Orthopaedic and Aerospace Fields	40
3.1	Schematic Process of SLM	47
3.2	Output Characteristic of SLM	48
3.3	Schematic Illustration of SLM 280 Machine	49
3.4	Functional Description of the Building Process	49
3.5	Process Related Factors of SLM Process	51
3.6	Scanning Pattern for SLM Process	52
3.7	Scanning Strategies in SLM Process	53
3.8	Various Types of Structure Geometries Used in SLM Process	57
3.9	Typical Support Teeth Concept	57

4.1	S/N Ratio for 800W, 2000mm/min and 400 μ m for Density	66
4.2	Caustic and Beam Intensity Distribution Measurement	67
4.3	Density Depending on Scanning Velocity and Laser Power and Δ ys = 0.15 mm	68
4.4	Densities by means of Cross Sections of SLM Samples Dep. on Scanning Velocity and Laser Power	69
4.5	Density based on Process Parameters	70
4.6	Cross Sections of Samples Built with different Hatch Spacing	70
4.7	Schematic Image of the Porous Section	71
4.8	S/N Ratio with Respect to Process Parameters for Porosity	72
4.9	Effect of Microhardness on Laser Related Parameters	74
4.10	Hardness depending on Scanning Velocity	75
4.11	Hardness Depending on Hatch Spacing	75
4.12	Tensile Strength based on Build up Direction	76
4.13	Effect of Particle Size and Heating Rate on the Sintered Density and Tensile Stress	77
4.14	Typical Tensile Curves Showing Yield Strength and Ductility	78
4.15	Building Directions of Test Samples	80
4.16	Stress-Strain Curve of SLMed-parts Produced in different Build Directions	81
4.17	Sliding Wear Rate (v), Average Size of the Si Particles (λ) and the Vickers Hardness (v) for the Al-12Si Cast, as-prepared SLM (300 K) and SLM Samples Annealed at different Temperature	83
5.1	Effect of Laser Related Parameter Variation in Mg-Al Alloy	87
5.2	Cross-section of: (a) the SLM Specimen; (b) the SLM + HIP	89
5.3	Effect of Energy Density on Porosity for Melted Samples	90
5.4	Effect of Energy Density on Hardness for Melted Samples	91
5.5	(a) XRD Patterns of SLMed and SLMed+ HIP Specimen, (b) Hardness of SLMed, SLMed + HIP and Forged Specimen, (c) SEM Image of SLMed (d) SEM Image of SLMed+ HIP Specimen	92
5.6	Microhardness for MEZ and LSM MEZ with Process Factors	93
5.7	Schematic Layout of LSM in Liquid Nitrogen	94
5.8	Microhardness along the Depth of Laser Surface Melting (LSM)	95

5.9	(a) & (b) Comparison of Strength and Elongation of SLMed and SLMed+ HIP Specimens, (c) & (d) Fracture Morphology of SLMed and SLMed+ HIP Specimen	96
5.10	(e1–e5), (f1–f5), Digital Image Correlation (DIC) Diagram of SLM and SLM + HIP Specimens (SLM + HIP Specimen)	97
5.11	Kinetics of Pit Formation	99
5.12	Corrosion Loss of Specimen	99
5.13	a) & b) Variation of Current Density with Potential	100
5.14	Potentiodynamic Polarization Curves of Laser Melted Layer and As-received AZ31B Mg Alloy	101
5.15	Comparison of the Wear Loss of MEZ & Surface Melted MEZ	103
6.1	(a) 900 J/ m, 100 mm/s (b) 450 J/ m, 200 mm/s; Microstructural Image with Laser Energy Density and Scan Speed	110
6.2	(a) 300 J/ m, 300 mm/s (b) 225 J/ m, 400 mm/s Microstructural Image with Laser Energy Density and Scan Speed	111
6.3	TiAl6V4 Powder Particles, 110x (left) and 1300x (right)	112
6.4	SLM-exposure of the Specimens (left) and Generated Specimens on the Substrate Plate (Right)	113
6.5	Loading–unloading Curves	115
6.6	Fatigue Specimen Processed by SLM	116
6.7	(a) & (b) Ti6Al4V SLM Microstructure along Build Direction	117
6.8	Fatigue Results	117
6.9	(a) Fatigue Crack Initiation at a Surface Defect and Partially Melted Particles, (b). Secondary Cracking in High Temperature Fatigue Fracture	118
6.10	(a) & (b) Specimen Produced in SLM and EBM Respectively	119
6.11	S-N Curve of Ti64 Samples (a) SLM and (b) EBM	119
6.12	Creep Specimen Processed by SLM	121
6.13	Creep Testing: Nominal Stress vs. Time to Failure	121
6.14	Creep Nominal Stresses vs. Larson Miller Parameter	122
6.15	Secondary Creep Strain Rate vs. Nominal Stress	122
6.16	Creep Test: Influence of Stress on Ductility at different Temperatures	123

6.17	Fracture surface of Specimen Creep Tested at: (a) 650 °C, 50 MPa (b) and 450 °C, 500 MPa	123
6.18	Stress-Strain Plots of Ti64 Samples (a) EBM Specimen, (b) SLM Specimen, Built in Vertical Orientation	125
6.19	Stress-Strain Plots of Ti64 Samples (a) EBM Specimen, (b) SLM Specimen, Built in Vertical Orientation	125
6.20	(a) COF and (b) Wear Rate of SLM-processed Ti Parts under different Processing Conditions	126
6.21	SEM Images of Worn Surfaces of SLM-processed Ti Parts with various Process Parameters	127
6.22	Crack Growth Curves for SLM-processed Ti-6-4 in different Conditions, Crack Growth Perpendicular to Build Direction	128
6.23	Crack Growth Curves for SLM-processed Ti-6-4 in different Conditions, Crack Growth Parallel to Build Direction	128
7.1	Inconel 718 Samples Built with different Laser Scanning Speeds	137
7.2	SEM Micrographs of (a) As-received Inconel 718 Powder Particles, (b) Their cross Sections, with White Arrows Indicating Pores in the Particles, and (c) Particle Size Distribution	138
7.3	(a) Variation of Porosity of SLM IN718 samples with different Laser Scanning Speeds and (b–f) Corresponding OM Images of Selected Samples: (b) 100, (c) 200, (d) 400, (e) 800, and (f) 1600 mm/s	139
7.4	Optical Micrographs for Cross-sections of SLM Samples Fabricated at different Scanning Speeds (a) 200, (b) 400, and (c) 800 mm/s	141
7.5	Powder Sampling Methodology	142
7.6	Picture Showing Manufacturing of Tests Pieces; Arrangement and Dimensions of Test Pieces	143
7.7	SEM Images of Powder (a) before and (b) after 14 Iterations Sieving and Drying. Comparison of Particle Size Distribution is shown in (c) in Terms of Relative (top) and Cumulative (bottom) Frequencies	144
7.8	EDS Spectra of IN 718 Powder Composition for the (a) First and (b) Last Iterations	145
7.9	Porosity Measurements Performed in Manufactured Samples	145
7.10	SEM Micrographs of IN718 (a) SLM Manufactured Samples on Cross Section, (b) Longitudinal Section	146

7.11	(a) Matrix γ and Phase Laves, (b and c) Corresponding EDS Analysis	147
7.12	Vickers Hardness in the XY Plane of SLM IN718 Samples with different Laser Scanning Speeds: (a) Average Hardness Value and (b) Hardness Distribution	147
7.13	Charpy Impact Tests Performed over Manufactured Samples	148
7.14	(a) SEM Analysis of Powder Particles, (b) Inconel 625 Grain Distribution	150
7.15	Geometry of the Specimens for Testing	150
7.16	S-N Curves for Polished and as-built Batches	151
7.17	Photograph of SLM-processed Inconel 718 Specimen	153
7.18	COFs of SLM-processed Inconel 718 Parts using various Processing Conditions	154
7.19	Wear Rates of SLM-processed Inconel 718 Parts Using different Processing Parameters	155
7.20	SEM Images Showing Morphologies of Worn Surfaces at various Laser Energy Densities: (a) 180 J/m; b) 275 J/m; (c) 300 J/m; (d) 330 J/m	156
7.21	Potentiodynamic Polarization Curves for the Inconel 718 Specimens Fabricated by different Processes in 3.5 wt% NaCl Solution	158
7.22	Inconel 718 Specimens Fabricated by different Processes in 3.5 wt% NaCl Solution with various Potential	159
7.23	Typical EIS Measurements for the ST3 and Rolled Inconel 718 Samples in 3.5 wt% NaCl Solution	161
7.24	Laser Scan Strategies: (i) Skywriting Function (Ref. 10), (ii) Layer Rotation by 66.7°, (iii) Checkerboard Pattern, and (iv) Stripe Pattern	162
7.25	(i) P1SRC Showing Porosity and Micro Crack Defects and (ii) P1RC without Periodic Porosity Defects for Prismatic Specimen	164
7.26	Micro-CT Images for Tensile samples Gauge Sections Indicating Porosity Defects over 50 μm in Size	164
7.27	Microstructure in the XY Plane as a Function of Laser Power and Energy Density	165
8.1	SEM Image of SS316L (a) Gas Atomized Powder Regular (b) Water Atomized Irregular Shaped Powder Particles	172
8.2	SEM Image at (a) $v = 150 \text{ mm/s}$; (b) is Local Magnification of (a). (c) $v = 60 \text{ mm/s}$; (d) $v = 20 \text{ mm/s}$ $P = 100\text{W}$ Constant	173

8.3	SEM Image of Specimen with different Process Parameter	174
8.4	SLM-produced Samples at (a) $v = 100$ mm/s; (b) $v = 200$ mm/s; (c) $v = 300$ mm/s; $h = 0.15$ mm, $d = 0.05$ mm and $P = 190$ W are Constants	175
8.5	SLM-produced Samples at different Hatch Spacing; $d = 0.05$ mm. $P = 190$ W and $v = 100$ mm/s are Constant	175
8.6	Samples at different Layer Thicknesses and Powder Kinds: (a) $d = 0.05$ mm, gas Atomization; (b) $d = 0.1$ mm, Gas Atomization; (c) $d = 0.1$ mm Water Atomization	176
8.7	Effect of Laser Power and Scan Speeds on Substrate Appearance of Line Spacing	177
8.8	Cross Sections of SS 316L Parts with different Condition	179
8.9	Size Distribution and SEM Image of 316L SS Powder Particles	180
8.10	Cylindrical Shaped Samples	181
8.11	Morphology of L929 Cells after Culture in different Extracts	182
8.12	MTT Proliferation Assay of Cells Grown for 24 h in the Test Article Extracts at Three Different Scanning Speeds	183
8.13	Hemolytic Rate of SLM 316L SS Parts at Three different Scanning Speeds	184
8.14	Micrographs of M3:2 HSS Powder in the Initial State	185
8.15	Micrograph of Sieved M3:2 High-speed Steel Powder Particles	185
8.16	Particle Size Distribution of the M3:2 High-speed Steel in the Initial and Reused States (after 30 cycles)	186
8.17	Samples build in different Directions	188
8.18	Fracture Toughness of 316L Stainless Steel Plotted against the Hardness HV	190
8.19	Stress-strain Curves for the SLM of SS 316L Built in different Directions	191
8.20	Dimensions of Upper and Lower Specimens	192
8.21	Schematic Layout of End Face Friction Tester	194
8.22	Coefficient of Friction versus Time for the Contact between SS 316L and Brass	195
8.23	Wear Rate Measured from the Brass Samples	195
8.24	CLSM Images of Surface Topography of SS 316L Sample	196

8.25	Energy Dispersive Spectrometer (EDS) Detects Brass Transfer from a SEM Image	196
8.26	CLSM Images Showing Contacting Surface of 316L Stainless Steel: (a) SLM Sample; (b) TP Sample	197
8.27	Coefficient of Friction Versus Time for the Contact between SS 316L and 38CrMoAl	197
8.28	Wear Rate Measured from SS316L	198
8.29	CLSM Images of Surface Topography of (a) Polished SLM Sample; (b) Polished TP Sample	198
8.30	CLSM Images of Cross Section of Polished Surface of (a) SLM Sample and (b) TP Sample	199
8.31	CLSM Image of the Surface Topography of the SLM Sample	199
8.32	EDS/SEM Results	200
8.33	Cyclic Potentiodynamic Polarization Curves	201
9.1	Examples of Composite Materials with different forms of Constituents and Distributions of the Reinforcements	205
9.2	Classification of Composites based on their Arrangements	206
9.3	Influence of Laser Energy Density on the Densification Rate and Cross Sectional Microstructure	210
9.4	CT Scanning Exhibition of the SLM Parts	213
9.5	SEM View of the x-y Cross Section of the SLM Parts	214
9.6	Schematic Illustration of the Thermal Stress and the Origin of Cracks within each Layer of an SLM-processed Component	215
9.7	Specimen Built with and without Rescanning Process	216
9.8	Effect of Laser Energy Density on Micro Hardness and Indentation Morphology of SLMed Processed Part	217
9.9	Characteristics of the Feedstock Powders	219
9.10	Images of Three-dimensional Model of Samples	220
9.11	Stress-strain Curves of as-fabricated Fe/SiC Composite and as-fabricated Pure Fe Specimen	221
9.12	Compressive True Stress-strain Curves for CP-Ti and Ti-TiB Composite Produced by SLM	222

9.13	(a) Variations of Friction Coefficient of Parts with different η (b) Wear Rate of Composite Parts with Applied Laser η	224
9.14	CPP Curves of SLMed-SS and SLMed-composite	225